YOUR DATA, ANYWHERE, ANYTIME

LogTag®

UTREL30-WiFi

30 Day WiFi Low Temperature Logger with Display

The LogTag® UTREL30-WiFi temperature data logger automatically uploads real-time temperature data to your LogTag® Online cloud account via your existing wireless network.

It features a large, easy-to-read display, along with many familiar attributes known from the LogTag® family of data loggers.

These include non-volatile memory for up to 16,129 temperature readings and a statistical memory, storing maximum and minimum reading as well as alarm duration for each of the last 30 days.

Accessories



2x AAA Batteries
Not Included



USB Cable
Included



*AC Adapter^*
Included



Wall Mount
Not Included

Buffer assembly
Not Included
(Silica sand recommended for temperatures below -40°C)

External Probe
Not Included (Required).

ST10S Probes are available with a 0.5m, 1.5m or 3m cable
ST10M Probes are available with a 1.5m or 3m cable
E.g. ST10M-15 for 1.5m or ST10M-30 for 3m cable

Compatible probes below:

ST10S	22mm tip length, ø5mm (Not recommended for use with buffer)
ST10M	65mm tip length, ø5mm.
STX50	5 Meter extension cable for ST10/ST100 sensors.

^US and EU adapter only

Features

Real-time data automatically uploaded via WiFi to the LogTag Online cloud.

Download data via LogTag Analyzer or as a PDF (no software required) when WiFi is unavailable.

Read current temperature and latest Min-Max temperature at a glance.

Check and reset Min-Max temperature reading at any time.

Audible alarm and flashing red LED signals a temperature alarm.

View alarm status for up to 30 days at a glance.



Can be powered by 2x AAA batteries (user replaceable) if not external powered.

Measure and store up to 16,000 readings – enough for 67 days at 6 minute logging.

Auto-pause function suspends alarm & statistic processing when the external sensor is unplugged.

Second battery backup via a coin cell to ensure no data is lost.

Applications

Vaccine & Pharmaceuticals

Industrial

Cold Storage

Clinic

Transportation

Refrigerated Containers

Specifications

Product Model	UTREL30-WiFi.
Sensor Measurement Range	-90°C to +40°C (-130°F to +104°F).
Operating Temperature Range	-30°C to +60°C (-22°F to +140°F).
Storage Temperature Range	0°C to +40°C (32°F to +104°F).
Rated Temperature Reading Resolution	0.1°C (0.2°F) for measurements -80°C to 10°C (-112°F to 50°F) 0.2°C (0.4°F) for measurements 10°C to 20°C (50°F to 68°F) and -90°C to -80°C (-130°F to -112°F) 0.3°C (0.5°F) for measurements 20°C to 30°C (68°F to 86°F) 0.5°C (0.9°F) for measurements 30°C to 40°C (86°F to 104°F) LogTag Analyzer® currently displays to one decimal place of °C or °F. The native resolution is what is stored in the LogTag®.
Rated Temperature Reading Accuracy	Better than ±0.5°C for -20°C to +10°C (-4°F to 50°F) Better than ±0.7°C for -50°C to -20°C (-58°F to -4°F) and +10°C to +30°C (50°F to 86°F) Better than ±1°C for -80°C to -50°C (-112°F to -58°F) and +30°C to +40°C (86°F to 104°F) Better than ±1.8°C for -90°C to -80°C (-130°F to -112°F)
Recording Capacity	16,129 temperature readings. 67 days at 6 minute logging. Day summary statistics memory (for display on LCD): up to 30 days of Min/Max/duration and alarm trigger statistics.
Sensor Reaction Time	Typically less than 2 minutes(T90) in moving air (1m/s) for ST10S type.
Sampling Interval	Configurable from 30 seconds to 18 hours.
Logging Start Options	Push button start (with configurable start delay from 1 minute to 72 hours) or specific date & time.
Download Time	Typically with full memory (16,129 readings) in less than 10 seconds.
Environmental	IP51 (when vertically mounted or hung with USB dust-cap in place).
Calibration	Factory calibrated using NIST equivalent reference equipment. Calibration certificate available on request.
Power Source	5V via micro USB socket or, 2 x 1.5V AAA batteries. CR2032 $LiMnO_2$ coin cell (backup logging function only).
Battery Life	Device should normally be powered via USB. AAA batteries provide backup power for up to 2 months.
Connection Interface	USB 2.0 / Micro-USB plug.
WiFi	IEEE 802.11 / WPA/WPA2 security.
Size	141mm(H) x 72mm(W) x 18mm(T).
Weight	158g with AAA batteries, (134g - excluding probe and AAA batteries).
Case Material	Polycarbonate

designed for 21CFR Part 11

RoHS COMPLIANT

Connection Software

Real-time data automatically uploaded via WiFi to the LogTag Online cloud.

For more information on LogTag Online, please visit our website:

logtagrecorders.com/online



Revision I (050422) © Copyright 2022, LogTag North America Inc. All rights reserved.
LogTag® is a registered trademark of LogTag North America Inc.
LogTag North America Inc. reserves the right to change this specification without notice.